

Back shell with groove for heatshrinkable shapes

Item number: BSH10-AC

Packing unit: 1




MECHANICAL PROPERTIES

Size:	10SL
Shell material:	Aluminum alloy
Surface:	Epoxy-polyurethane
Type of surface:	Varnished
Thickness of surface treatment [μ]:	13-16 μ
Surface colour:	Black
Corrosion resistance [h]:	500
Operation temperature [$^{\circ}$ C]:	-55 - +125
Temperature shock [$^{\circ}$ C]:	-55 - +125
Conductivity (M Ω):	Non conductive
EMI:	No
Material sealing ring:	Silicone

STANDARDS

Fire protection class EN 45545-2:	R22:HL1/HL2/HL3 R23: HL1/HL2/HL3
Protection class EN 60529 (mounted):	IP69
RoHS-compliant:	compliant
REACH-compliant:	SVHC substances, no

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	20
D2 Ø [mm]:	15.5
D3 Ø [mm]:	13.3
d1 Ø [mm]:	8.0
L1 [mm]:	18.0

DIMENSIONS

L2 [mm]:	11.7
L3 [mm]:	3.5
N1:	5/8"-24 UNEF 2B

· Please contact your Gimota partner for other shell materials or surface coatings.