

Backshell with groove for heatshrinkable shapes

Item number: BSH40-AA
Product weight (kg): 0.0965 kg
Packing unit: 1




MECHANICAL PROPERTIES

Size:	40
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	10-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90
Temperature shock [°C]:	-55 - +125
Conductivity (M Ω):	≤ 0.5
EMI:	Yes
Material sealing ring:	Silicone

STANDARDS

Fire protection class EN 45545-2:	R22:HL1/HL2/HL3 R23: HL1/HL2/HL3
Protection class EN 60529 (mounted):	IP69
RoHS-compliant:	compliant
REACH-compliant:	SVHC substances, no

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	64
D2 Ø [mm]:	57.8
D3 Ø [mm]:	52.5
d1 Ø [mm]:	48.2
L1 [mm]:	45.0



DIMENSIONS

L2 [mm]:	15.2
L3 [mm]:	3.5
N1:	2 5/16"-16 UNEF 2B

· Please contact your Gimota partner for other shell materials or surface coatings.