

Plug with bayonet coupling nut

Series GB

Item number: GB60-28-21SN-EAC

Product weight (kg): 0.0899 kg

Packing unit: 1



MECHANICAL PROPERTIES

Size:	28
Contact type:	Socket
Number of coding options:	4
Number of contacts:	37
Number of contacts, size 16:	37
Shell material:	Aluminum alloy
Surface:	Epoxy-polyurethane
Type of surface:	Varnished
Thickness of surface treatment [μ]:	13-16 μ
Surface colour:	Black
Corrosion resistance [h]:	500
Operation temperature [°C]:	-55 - +125
Temperature shock [°C]:	-55 - +125

MECHANICAL PROPERTIES

Conductivity (MΩ): Non conductive

EMI: No

Material sealing ring: Silicone

Coupling-torque to lock [Nm]: max. 7.0

Coupling-torque to open [Nm]: min. 2.7

THERMAL PROPERTIES

Material contact insert: Ethylene acrylate GXF / thermoplastic

Operating temperature insert [°C]: -55 - +150

ELECTRICAL PROPERTIES

Operating voltage DC [V]: 700

Operating voltage AC [V]: 500

Test voltage AC [V]: 2000

Insulation resistance (mΩ): ≥ 5000

Insulation creepage distance [mm]: ≥ 3.2

Voltage class: MIL-DTL-5015

ELECTRICAL PROPERTIES CONTACTS

Size 16 - rated current (continuous) [A]: 13

Size 16 - maximum current (short-term) [A]: 22


Size 16 - test current [A]: 20

STANDARDS

Fire protection class EN 45545-2:

R23/HL3

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	54
L1 [mm]:	36
N1:	1 5/8"-18 UNEF 2A
X1 [mm]:	9

Socket contact size 16, 0.75mm²

Item number: 10-40556-075AU

Product weight (kg): 0.0015 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.75
Wire section [AWG]:	18
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.2
d1 Ø [mm]:	1.35
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 16, 1.0mm²

Item number: 10-40556AU

Product weight (kg): 0.0016 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	1
Wire section [AWG]:	16
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.9
d1 Ø [mm]:	1.8
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 16, 1.5mm²

Item number: 10-40556-20-1AU

Product weight (kg): 0.0016 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	1.5
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.62
d1 Ø [mm]:	1.75
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 16, 0.25 - 0.5mm²

Item number: 10-40556-05AU

Product weight (kg): 0.0002 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.25 - 0.5
Wire section [AWG]:	22 - 20
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.15
d1 Ø [mm]:	1.1
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4