

Power connector housing, surface-mounted, max. 960 A

3-pole version, without accessory slot

Item number: GMPH-3S1N-BR-30-S

Packing unit: 1



MECHANICAL PROPERTIES

Design:	Surface-mounted housing
Number of contacts:	3
Contact type:	Socket contact
Shell material:	Aluminum alloy
Surface:	Hard anodising
Surface colour:	Black
Locking mode:	Screwed
Screw material:	Stainless steel
Operation temperature [°C]:	-55 - +180
Material sealing ring:	MVQ
Number of mating cycles (min.):	500
No. of cable entrances:	3
Cable strain relief:	Cable gland

Material contact insert:	High temperature thermoplastic
Operating temperature insert [°C]:	-55 - +180

ELECTRICAL PROPERTIES

Operating voltage [V]:	3600
EMI:	Yes



Fire protection class EN 45545-2:	R22:HL1/HL2/HL3 R23: HL1/HL2/HL3
Protection class EN 60529:	IP68
RoHS-compliant:	Yes
REACH-compliant:	Yes

Socket contact 960A, 240mm²

Item number: GMPC-30S-240AG

Packing unit: 1



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket contact
---------------	----------------

Rated current (continuous) [A]:	960
---------------------------------	-----

Contact Material:	CU alloy
-------------------	----------

Coating:	Silver
----------	--------

Protective layer:	Silver plated
-------------------	---------------


MECHANICAL PROPERTIES CONTACTS

Type of manufacture:	Turned
Connection type:	Crimp
Wire section [mm²]:	240
REACH-compliant:	SVHC substances, yes - Lead
RoHS-compliant:	Compliant with exception 6c (copper alloy $\leq 4\%$ lead)

STANDARDS

RoHS-compliant:	Compliant with exception 6c (copper alloy $\leq 4\%$ lead)
REACH-compliant:	SVHC substances, yes - Lead

DIMENSIONS



Socket contact 960A, 300mm²

Item number: GMPC-30S-300AG

Packing unit: 1



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket contact
---------------	----------------

Rated current (continuous) [A]:	960
---------------------------------	-----

Contact Material:	CU alloy
-------------------	----------

Coating:	Silver
----------	--------

Protective layer:	Silver plated
-------------------	---------------

MECHANICAL PROPERTIES CONTACTS

Type of manufacture:	Turned
Connection type:	Crimp
Wire section [mm²]:	300
REACH-compliant:	SVHC substances, yes - Lead
RoHS-compliant:	Compliant with exception 6c (copper alloy $\leq 4\%$ lead)

STANDARDS

RoHS-compliant:	Compliant with exception 6c (copper alloy $\leq 4\%$ lead)
REACH-compliant:	SVHC substances, yes - Lead

DIMENSIONS

