

Cable receptacle

Series GR

Item number: GR11-20-A48PN-EAA

Packing unit: 1



MECHANICAL PROPERTIES

Size:	20
Contact type:	Pin
Number of coding options:	2
Number of contacts:	19
Number of contacts, size 16:	19
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90
Temperature shock [°C]:	-55 - +125

MECHANICAL PROPERTIES

Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock [Nm]:	max. 5.0
Coupling-torque to open [Nm]:	min. 1.5

THERMAL PROPERTIES

Material contact insert:	Ethylene acrylate GXF
Operating temperature insert [°C]:	-55 - +150

ELECTRICAL PROPERTIES

Operating voltage DC [V]:	250
Operating voltage AC [V]:	200
Test voltage AC [V]:	1000
Insulation resistance (mΩ):	≥ 5000
Insulation creepage distance [mm]:	≥ 1.6
Voltage class:	MIL-DTL-5015

ELECTRICAL PROPERTIES CONTACTS




Size 16 - rated current (continuous) [A]:	13
Size 16 - maximum current (short-term) [A]:	22
Size 16 - test current [A]:	20

STANDARDS

Fire protection class EN 45545-2:

R23/HL3

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	34.2
D2 Ø [mm]:	37.0
L1 [mm]:	34.3
L2 [mm]:	19.0
L3 [mm]:	4.0
N1:	1 1/8"-18 UNEF 2A
X1 [mm]:	9.0

- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method Electrical conductivity acc. MIL 1344A, Test 3007

Pin contact size 16, 1.0mm²

Item number: 10-40557AU

Product weight (kg): 0.001 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
---------------	-----

Maximum current (short-term) [A]:	22
-----------------------------------	----

Test current [A]:	20
-------------------	----

Rated current (continuous) [A]:	13
---------------------------------	----

Contact Material:	CU alloy
-------------------	----------

Protective layer:	Gold plated, 0.5μm
-------------------	--------------------

Connection type:	Crimp
------------------	-------

Wire section [mm ²]:	1
----------------------------------	---

Wire section [AWG]:	16
---------------------	----

Stripping length [mm]:	7
------------------------	---

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.9
D3 Ø [mm]:	1.6
d1 Ø [mm]:	1.8
L1 [mm]:	32
T1 [mm]:	6.4

Pin contact size 16, 1.5mm²

Item number: 10-40557-20-1AU

Product weight (kg): 0.001 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	1.5
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.62
D3 Ø [mm]:	1.6
d1 Ø [mm]:	1.75
L1 [mm]:	32
T1 [mm]:	6.4

Pin contact size 16, 0.25 -0.5mm²

Item number: 10-40557-05AU

Product weight (kg): 0.0009 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.25 - 0.5
Wire section [AWG]:	22 - 20
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.15
D3 Ø [mm]:	1.6
d1 Ø [mm]:	1.1
L1 [mm]:	32
T1 [mm]:	6.4

Pin contact size 16, 0.75mm²

Item number: 10-40557-075AU

Product weight (kg): 0.0009 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.75
Wire section [AWG]:	18
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.2
D3 Ø [mm]:	1.6
d1 Ø [mm]:	1.35
L1 [mm]:	32
T1 [mm]:	6.4