


Plug with bayonet coupling nut

Series GR

Item number: GR60-32-15PN-EAA

Packing unit: 1



MECHANICAL PROPERTIES

Size:	32
Contact type:	Pin
Number of coding options:	4
Number of contacts:	8
Number of contacts, size 0:	2
Number of contacts, size 12:	6
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [$^{\circ}$ C]:	-55 - +90

MECHANICAL PROPERTIES

Temperature shock [°C]: -55 - +125

Conductivity (MΩ): ≤ 0.5

Coupling-torque to lock [Nm]: max. 8.0

Coupling-torque to open [Nm]: min. 3.6

THERMAL PROPERTIES

Material contact insert: Ethylene acrylate GXF

Operating temperature insert [°C]: -55 - +150

ELECTRICAL PROPERTIES

Operating voltage DC [V]: 1250

Operating voltage AC [V]: 900

Test voltage AC [V]: 2800

Insulation resistance (mΩ): ≥ 5000

Insulation creepage distance [mm]: ≥ 4.8

Voltage class: MIL-DTL-5015



ELECTRICAL PROPERTIES CONTACTS

Size 0 - rated current (continuous) [A]:	200
Size 0 - maximum current (short-term) [A]:	300
Size 0 - test current [A]:	240
Size 12 - rated current (continuous) [A]:	23
Size 12 - maximum current (short-term) [A]:	41
Size 12 - test current [A]:	35

STANDARDS

Fire protection class EN 45545-2:	R23/HL3
-----------------------------------	---------

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	60
L1 [mm]:	38.0
N1:	1 7/8"-16 UN 2A
X1 [mm]:	10.5


- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method Electrical conductivity acc. MIL 1344A, Test 3007

Pin contact size 12, 0.5mm²

Item number: 10-40561-11AU

Product weight (kg): 0.0022 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	41
Test current [A]:	35
Rated current (continuous) [A]:	23
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.5
Wire section [AWG]:	20
Stripping length [mm]:	9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	3
D3 Ø [mm]:	2.4
d1 Ø [mm]:	1.1
L1 [mm]:	38
T1 [mm]:	8.5

Pin contact size 0, 25mm²

Item number: 10-660-0-252G76

Product weight (kg): 0.0376 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	245
Test current [A]:	200
Rated current (continuous) [A]:	150
Contact Material:	CU alloy
Protective layer:	Silver plated, 3.5µm
Connection type:	Crimp
Wire section [mm ²]:	25
Stripping length [mm]:	18

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	15
D2 Ø [mm]:	11.7
D3 Ø [mm]:	9
d1 Ø [mm]:	7.6
L1 [mm]:	52
T1 [mm]:	17

Pin contact size 12, 2.5mm²

Item number: 10-40561-22AU

Product weight (kg): 0.0023 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Pin

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm


Connection type: Crimp

Wire section [mm²]: 2.5

Wire section [AWG]: 14

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.95
D3 Ø [mm]:	2.4
d1 Ø [mm]:	2.25
L1 [mm]:	38
T1 [mm]:	8.5

Pin contact size 12, 6.0mm²

Item number: 10-40561-38AU

Product weight (kg): 0.0023 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	41
Test current [A]:	35
Rated current (continuous) [A]:	23
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	6
Wire section [AWG]:	10
Stripping length [mm]:	9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	4.75
D3 Ø [mm]:	2.4
d1 Ø [mm]:	3.5
L1 [mm]:	38
T1 [mm]:	8.5

Pin contact size 12, 4.0mm²

Item number: 10-40561-30AU

Product weight (kg): 0.0025 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Pin

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5μm


Connection type: Crimp

Wire section [mm²]: 4

Wire section [AWG]: 12 - 10

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	4.75
D3 Ø [mm]:	2.4
d1 Ø [mm]:	2.95
L1 [mm]:	38
T1 [mm]:	8.5

Pin contact size 0, 50mm²

Item number: 10-660-0-502G10

Product weight (kg): 0.0441 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	245
Test current [A]:	200
Rated current (continuous) [A]:	150
Contact Material:	CU alloy
Protective layer:	Silver plated, 3.5µm
Connection type:	Crimp
Wire section [mm ²]:	50
Wire section [AWG]:	0
Stripping length [mm]:	22

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	15
D2 Ø [mm]:	14.6
D3 Ø [mm]:	9
d1 Ø [mm]:	10.5
L1 [mm]:	56
T1 [mm]:	20.5

Pin contact size 12, 1.5mm²

Item number: 10-40561-18AU

Product weight (kg): 0.0024 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	41
Test current [A]:	35
Rated current (continuous) [A]:	23
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	1.5
Wire section [AWG]:	18 - 16
Stripping length [mm]:	9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.95
D3 Ø [mm]:	2.4
d1 Ø [mm]:	1.75
L1 [mm]:	38
T1 [mm]:	8.5

Pin contact size 0, 16mm²

Item number: 10-660-0-162G62

Product weight (kg): 0.0334 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	245
Test current [A]:	200
Rated current (continuous) [A]:	150
Contact Material:	CU alloy
Protective layer:	Silver plated, 3.5µm
Connection type:	Crimp
Wire section [mm ²]:	16
Stripping length [mm]:	17

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	15
D2 Ø [mm]:	9.3
D3 Ø [mm]:	9
d1 Ø [mm]:	6.2
L1 [mm]:	51
T1 [mm]:	17

Pin contact size 12, 0.75 - 1.0mm²

Item number: 10-40561-15AU

Product weight (kg): 0.0022 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Pin

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm


Connection type: Crimp

Wire section [mm²]: 0.75 - 1.0

Wire section [AWG]: 22 - 18

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.35
D3 Ø [mm]:	2.4
d1 Ø [mm]:	1.45
L1 [mm]:	38
T1 [mm]:	8.5

Pin contact size 0, 35mm²

Item number: 10-660-0-352G89

Product weight (kg): 0.0402 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Maximum current (short-term) [A]:	245
Test current [A]:	200
Rated current (continuous) [A]:	150
Contact Material:	CU alloy
Protective layer:	Silver plated, 3.5µm
Connection type:	Crimp
Wire section [mm ²]:	35
Wire section [AWG]:	2 - 1
Stripping length [mm]:	18

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	15
D2 Ø [mm]:	13
D3 Ø [mm]:	9
d1 Ø [mm]:	8.9
L1 [mm]:	53
T1 [mm]:	19