

Plug with bayonet coupling nut, for EMI applications

Series GR

Item number: GR601-14S-7SN-EAA

Packing unit: 1



MECHANICAL PROPERTIES

Size:	14S
Contact type:	Socket
Number of coding options:	3
Number of contacts:	3
Number of contacts, size 16s:	3
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90

MECHANICAL PROPERTIES

Temperature shock [°C]:	-55 - +125
Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock [Nm]:	max. 1.8
Coupling-torque to open [Nm]:	min. 0.55

THERMAL PROPERTIES

Material contact insert:	Ethylene acrylate GXF
Operating temperature insert [°C]:	-55 - +150

ELECTRICAL PROPERTIES

Operating voltage DC [V]:	700
Operating voltage AC [V]:	500
Test voltage AC [V]:	2000
Insulation resistance (mΩ):	≥ 5000
Insulation creepage distance [mm]:	≥ 3.2
Voltage class:	MIL-DTL-5015

ELECTRICAL PROPERTIES CONTACTS

Size 16S - rated current (continuous) [A]:	13
Size 16S - maximum current (short-term) [A]:	22
Size 16S - test current [A]:	20

STANDARDS

Fire protection class EN 45545-2:

R23/HL3

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	30
L1 [mm]:	24.6
N1:	3/4"-20 UNEF 2A
X1 [mm]:	9.0


- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method
- Electrical conductivity acc. MIL 1344A, Test 3007

Socket contact size 16S, 0.25 - 0.5mm²

Item number: 10-40552-05AU

Product weight (kg): 0.0001 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.25 - 0.5
Wire section [AWG]:	22 - 20
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.15
d1 Ø [mm]:	1.1
d2 Ø [mm]:	1.6
L1 [mm]:	27
T1 [mm]:	6.4

Socket contact size 16S, 0.75 - 1.5mm²

Item number: 10-40552AU

Product weight (kg): 0.0009 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
Maximum current (short-term) [A]:	22
Test current [A]:	20
Rated current (continuous) [A]:	13
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.5µm
Connection type:	Crimp
Wire section [mm ²]:	0.75 - 1.5
Wire section [AWG]:	16
Stripping length [mm]:	7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.62
d1 Ø [mm]:	1.75
d2 Ø [mm]:	1.6
L1 [mm]:	27
T1 [mm]:	6.4