

Plug with rubber coated coupling nut, for EMI applications

Series GR

Item number: GR604-18-11SN-EAA

Packing unit: 1



MECHANICAL PROPERTIES

Size:	18
Contact type:	Socket
Number of coding options:	2
Number of contacts:	5
Number of contacts, size 12:	5
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90

MECHANICAL PROPERTIES

Temperature shock [°C]:	-55 - +125
Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock [Nm]:	max. 4.0
Coupling-torque to open [Nm]:	min. 1.0

THERMAL PROPERTIES

Material contact insert:	Ethylene acrylate GXF
Operating temperature insert [°C]:	-55 - +150

ELECTRICAL PROPERTIES

Operating voltage AC [V]:	130/250
Insulation resistance (mΩ):	≥ 5000
Voltage class:	SEV-EN60998-1
Contact numbers:	All
Operating voltage DC [V]:	700
Operating voltage AC [V]:	500
Test voltage AC [V]:	2000
Insulation resistance (mΩ):	≥ 5000
Insulation creepage distance [mm]:	≥ 3.2
Voltage index:	MIL-DTL-5015

ELECTRICAL PROPERTIES CONTACTS

Size 12 - rated current (continuous) [A]:	23
---	----


Size 12 - maximum current (short-term) [A]:	41
---	----

Size 12 - test current [A]:	35
-----------------------------	----

STANDARDS

Fire protection class EN 45545-2:	R23/HL3
-----------------------------------	---------

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	49
L1 [mm]:	39.0
N1:	1"-20 UNEF 2A
X1 [mm]:	9.0

- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method Electrical conductivity acc. MIL 1344A, Test 3007

Socket contact size 12, 6.0mm²

Item number: 10-40560-38AU

Product weight (kg): 0.0033 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
---------------	--------

Maximum current (short-term) [A]:	41
-----------------------------------	----

Test current [A]:	35
-------------------	----

Rated current (continuous) [A]:	23
---------------------------------	----

Contact Material:	CU alloy
-------------------	----------

Protective layer:	Gold plated, 0.5µm
-------------------	--------------------

Connection type:	Crimp
------------------	-------

Wire section [mm ²]:	6
----------------------------------	---

Wire section [AWG]:	10
---------------------	----

Stripping length [mm]:	9
------------------------	---

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	4.75
d1 Ø [mm]:	3.5
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 1.5mm²

Item number: 10-40560-18AU

Product weight (kg): 0.0033 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 1.5

Wire section [AWG]: 18 - 16

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.95
d1 Ø [mm]:	1.75
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 0.75 - 1.0mm²

Item number: 10-40560-15AU

Product weight (kg): 0.0032 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 0.75 - 1.0

Wire section [AWG]: 22 - 18

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.35
d1 Ø [mm]:	1.45
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 4.0mm²

Item number: 10-40560-30AU

Product weight (kg): 0.0035 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 4

Wire section [AWG]: 12 - 10

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	4.75
d1 Ø [mm]:	2.95
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 0.5mm²

Item number: 10-40560-11AU

Product weight (kg): 0.0031 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 0.5

Wire section [AWG]: 20

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3
d1 Ø [mm]:	1.1
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 2.5mm²

Item number: 10-40560-22AU

Product weight (kg): 0.0033 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 2.5

Wire section [AWG]: 14

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.95
d1 Ø [mm]:	2.25
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5