

Plug with rubber coated coupling nut, for EMI applications

Series GR

Item number: GR604-36-7SN-EAA
Packing unit: 1



MECHANICAL PROPERTIES

Size:	36
Contact type:	Socket
Number of coding options:	4
Number of contacts:	47
Number of contacts, size 12:	7
Number of contacts, size 16:	40
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200

MECHANICAL PROPERTIES

Operation temperature [°C]:	-55 - +90
Temperature shock [°C]:	-55 - +125
Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock [Nm]:	max. 9.0
Coupling-torque to open [Nm]:	min. 4.5

THERMAL PROPERTIES

Material contact insert:	Ethylene acrylate GXF
Operating temperature insert [°C]:	-55 - +150

ELECTRICAL PROPERTIES

Operating voltage DC [V]:	700
Operating voltage AC [V]:	500
Test voltage AC [V]:	2000
Insulation resistance (MΩ):	≥ 5000
Insulation creepage distance [mm]:	≥ 3.2
Voltage class:	MIL-DTL-5015


ELECTRICAL PROPERTIES CONTACTS

Size 12 - rated current (continuous) [A]:	23
Size 12 - maximum current (short-term) [A]:	41
Size 12 - test current [A]:	35
Size 16 - rated current (continuous) [A]:	13
Size 16 - maximum current (short-term) [A]:	22
Size 16 - test current [A]:	20

STANDARDS

Fire protection class EN 45545-2:	R23/HL3
-----------------------------------	---------

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	82
L1 [mm]:	41.0
N1:	2 1/16"-16 UN 2A
X1 [mm]:	11.3

- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1Temperature shock tested acc. MIL 202F, 107G MethodElectrical conductivity acc. MIL 1344A, Test 3007

Socket contact size 16, 0.25 - 0.5mm²

Item number: 10-40556-05AU

Product weight (kg): 0.0002 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Socket
---------------	--------

Maximum current (short-term) [A]:	22
-----------------------------------	----

Test current [A]:	20
-------------------	----

Rated current (continuous) [A]:	13
---------------------------------	----

Contact Material:	CU alloy
-------------------	----------

Protective layer:	Gold plated, 0.5µm
-------------------	--------------------

Connection type:	Crimp
------------------	-------

Wire section [mm ²]:	0.25 - 0.5
----------------------------------	------------

Wire section [AWG]:	22 - 20
---------------------	---------

Stripping length [mm]:	7
------------------------	---

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.15
d1 Ø [mm]:	1.1
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 12, 2.5mm²

Item number: 10-40560-22AU

Product weight (kg): 0.0033 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 2.5

Wire section [AWG]: 14

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.95
d1 Ø [mm]:	2.25
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 1.5mm²

Item number: 10-40560-18AU

Product weight (kg): 0.0033 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 1.5

Wire section [AWG]: 18 - 16

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.95
d1 Ø [mm]:	1.75
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 16, 0.75mm²

Item number: 10-40556-075AU

Product weight (kg): 0.0015 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 22

Test current [A]: 20

Rated current (continuous) [A]: 13

Contact Material: CU alloy

Protective layer: Gold plated, 0.5μm

Connection type: Crimp

Wire section [mm²]: 0.75

Wire section [AWG]: 18

Stripping length [mm]: 7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.2
d1 Ø [mm]:	1.35
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 16, 1.0mm²

Item number: 10-40556AU

Product weight (kg): 0.0016 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 22

Test current [A]: 20

Rated current (continuous) [A]: 13

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 1

Wire section [AWG]: 16

Stripping length [mm]: 7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.9
d1 Ø [mm]:	1.8
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 12, 6.0mm²

Item number: 10-40560-38AU

Product weight (kg): 0.0033 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 6

Wire section [AWG]: 10

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	4.75
d1 Ø [mm]:	3.5
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 4.0mm²

Item number: 10-40560-30AU

Product weight (kg): 0.0035 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5μm

Connection type: Crimp

Wire section [mm²]: 4

Wire section [AWG]: 12 - 10

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.8
D2 Ø [mm]:	4.75
d1 Ø [mm]:	2.95
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 16, 1.5mm²

Item number: 10-40556-20-1AU

Product weight (kg): 0.0016 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 22

Test current [A]: 20

Rated current (continuous) [A]: 13

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 1.5

Stripping length [mm]: 7

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.1
D2 Ø [mm]:	2.62
d1 Ø [mm]:	1.75
d2 Ø [mm]:	1.6
L1 [mm]:	37
T1 [mm]:	6.4

Socket contact size 12, 0.5mm²

Item number: 10-40560-11AU

Product weight (kg): 0.0031 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 0.5

Wire section [AWG]: 20

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3
d1 Ø [mm]:	1.1
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5

Socket contact size 12, 0.75 - 1.0mm²

Item number: 10-40560-15AU

Product weight (kg): 0.0032 kg

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type: Socket

Maximum current (short-term) [A]: 41

Test current [A]: 35

Rated current (continuous) [A]: 23

Contact Material: CU alloy

Protective layer: Gold plated, 0.5µm

Connection type: Crimp

Wire section [mm²]: 0.75 - 1.0

Wire section [AWG]: 22 - 18

Stripping length [mm]: 9

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	4.8
D2 Ø [mm]:	3.35
d1 Ø [mm]:	1.45
d2 Ø [mm]:	2.4
L1 [mm]:	38
T1 [mm]:	8.5