

# Cable receptacle

Series GS

Item number: GS11-40-63SN-EAA

Packing unit: 1



## MECHANICAL PROPERTIES

|                                           |                |
|-------------------------------------------|----------------|
| Size:                                     | 40             |
| Contact type:                             | Socket         |
| Number of coding options:                 | 4              |
| Number of contacts:                       | 61             |
| Number of contacts, size 16:              | 61             |
| Shell material:                           | Aluminum alloy |
| Surface:                                  | Zinc           |
| Type of surface:                          | Passivated     |
| Thickness of surface treatment [ $\mu$ ]: | 12-15 $\mu$    |
| Surface colour:                           | Black          |
| Corrosion resistance [h]:                 | 200            |
| Operation temperature [°C]:               | -55 - +90      |
| Temperature shock [°C]:                   | -55 - +125     |

## MECHANICAL PROPERTIES

|                               |           |
|-------------------------------|-----------|
| Conductivity (MΩ):            | ≤ 0.5     |
| EMI:                          | Yes       |
| Coupling-torque to lock [Nm]: | max. 10.0 |
| Coupling-torque to open [Nm]: | min. 5.9  |

## THERMAL PROPERTIES

|                                    |                       |
|------------------------------------|-----------------------|
| Material contact insert:           | Ethylene acrylate GXF |
| Operating temperature insert [°C]: | -55 - +150            |

## ELECTRICAL PROPERTIES

|                                    |               |
|------------------------------------|---------------|
| Operating voltage AC [V]:          | 130/250       |
| Insulation resistance (mΩ):        | ≥ 5000        |
| Voltage class:                     | SEV-EN60998-1 |
| Contact numbers:                   | All           |
| Operating voltage DC [V]:          | 700           |
| Operating voltage AC [V]:          | 500           |
| Test voltage AC [V]:               | 2000          |
| Insulation resistance (mΩ):        | ≥ 5000        |
| Insulation creepage distance [mm]: | ≥ 3.2         |
| Voltage index:                     | MIL-DTL-5015  |

## ELECTRICAL PROPERTIES CONTACTS




Size 16 - rated current (continuous) [A]: 13

Size 16 - maximum current (short-term) [A]: 22

Size 16 - test current [A]: 20

Fire protection class EN 45545-2: R23/HL3

## DIMENSIONS



## DIMENSIONS

D1 Ø [mm]: 66

D2 Ø [mm]: 68.5

L1 [mm]: 37.5

## DIMENSIONS

|          |                  |
|----------|------------------|
| L2 [mm]: | 22.2             |
| L3 [mm]: | 4.0              |
| N1:      | 2 5/16"-16 UN 2A |
| X1 [mm]: | 11.3             |

- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method Electrical conductivity acc. MIL 1344A, Test 3007