

Receptacle with flange

Series GS

Item number: GS321-24-07PN-EAA

Packing unit: 1



MECHANICAL PROPERTIES

Size:	24
Contact type:	Pin
Number of coding options:	2
Number of contacts:	7
Number of contacts, size 12:	7
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90
Temperature shock [°C]:	-55 - +125

MECHANICAL PROPERTIES

Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock [Nm]:	max. 6.5
Coupling-torque to open [Nm]:	min. 2.0

THERMAL PROPERTIES

Material contact insert:	Ethylene acrylate GXF
Operating temperature insert [°C]:	-55 - +150

ELECTRICAL PROPERTIES

Operating voltage AC [V]:	130/250*
Voltage class:	SEV-EN60998-1
Contact numbers:	All
Operating voltage DC [V]:	1250
Operating voltage AC [V]:	900
Test voltage AC [V]:	2800
Insulation resistance (mΩ):	≥ 5000
Insulation creepage distance [mm]:	≥ 4.8
Voltage index:	MIL-DTL-5015

ELECTRICAL PROPERTIES CONTACTS




Size 12 - rated current (continuous) [A]: 23

Size 12 - maximum current (short-term) [A]: 41

Size 12 - test current [A]: 35

Fire protection class EN 45545-2: R23/HL3

DIMENSIONS



DIMENSIONS

D1 Ø [mm]: 41

L1 [mm]: 38.8

L2 [mm]: 23.1

DIMENSIONS

L3 [mm]:	4.0
N1:	1 3/8"-18 UNEF 2A
T1 [mm]:	3.7
X1 [mm]:	9.0
S1 [mm]:	44.5
R1 [mm]:	35

-
- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
 - Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
 - Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method
 - Electrical conductivity acc. MIL 1344A, Test 3007