

Plug with bayonet coupling nut, for EMI applications

Series GS

Item number: GS601-22-22SN-EAA
Packing unit: 1



MECHANICAL PROPERTIES

Size:	22
Contact type:	Socket
Number of coding options:	3
Number of contacts:	4
Number of contacts, size 8H:	4
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90

MECHANICAL PROPERTIES

Temperature shock [°C]:	-55 - +125
Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock [Nm]:	max. 6.0
Coupling-torque to open [Nm]:	min. 1.5

THERMAL PROPERTIES

Material contact insert:	Ethylene acrylate GXF
Operating temperature insert [°C]:	-55 - +150

ELECTRICAL PROPERTIES

Operating voltage DC [V]:	700
Operating voltage AC [V]:	500
Test voltage AC [V]:	2000
Insulation resistance (mΩ):	≥ 5000
Insulation creepage distance [mm]:	≥ 3.2
Voltage class:	MIL-DTL-5015


ELECTRICAL PROPERTIES CONTACTS

Size 8H - rated current (continuous) [A]:	56
Size 8H - maximum current (short-term) [A]:	90
Size 8H - test current [A]:	72

Fire protection class EN 45545-2:

R23/HL3

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	44
L1 [mm]:	36.0
N1:	1 1/4"-18 UNEF 2A
X1 [mm]:	9.0

· Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
 Voltage classes tested acc. MIL-DTL-5015 Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 /
 · 37 Corrosion resistance tested acc. MIL 1344A Test 101.1 Temperature shock tested acc. MIL 202F, 107G Method Electrical
 conductivity acc. MIL 1344A, Test 3007