

Plug with rubber coated coupling nut

Series GS

Item number: GS602-40-A4PN-EAA

Packing unit: 1



MECHANICAL PROPERTIES

Size:	40
Contact type:	Pin
Number of contacts:	4
Number of contacts, size 0:	4
Shell material:	Aluminum alloy
Surface:	Zinc
Type of surface:	Passivated
Thickness of surface treatment [μ]:	12-15 μ
Surface colour:	Black
Corrosion resistance [h]:	200
Operation temperature [°C]:	-55 - +90

MECHANICAL PROPERTIES

Temperature shock [°C]: -55 - +125

Conductivity (MΩ): ≤ 0.5

Coupling-torque to lock [Nm]: max. 10.0

Coupling-torque to open [Nm]: min. 5.9

THERMAL PROPERTIES

Material contact insert: Ethylene acrylate GXF

Operating temperature insert [°C]: -55 - +150

ELECTRICAL PROPERTIES

Operating voltage AC [V]: 750

Insulation resistance (mΩ): ≥ 5000

Voltage class: ABB

Contact numbers: All

Operating voltage DC [V]: 1750

Operating voltage AC [V]: 1250

Test voltage AC [V]: 3500

Insulation resistance (mΩ): ≥ 5000

Insulation creepage distance [mm]: ≥ 6.3

Voltage index: MIL-DTL-5015

ELECTRICAL PROPERTIES CONTACTS


Size 0 - rated current (continuous) [A]:	200
--	-----

Size 0 - maximum current (short-term) [A]:	300
--	-----

Size 0 - test current [A]:	240
----------------------------	-----

Fire protection class EN 45545-2:	R23/HL3
-----------------------------------	---------

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	88
L1 [mm]:	41.0
N1:	2 5/16"-16 UN 2A
X1 [mm]:	11.3

- Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.
- Voltage classes tested acc. MIL-DTL-5015Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37
- Corrosion resistance tested acc. MIL 1344A Test 101.1Temperature shock tested acc. MIL 202F, 107G MethodElectrical conductivity acc. MIL 1344A, Test 3007