

GTM12 bulkhead mounting , a-code, pin

according EN 61076-2-101

Item number: GTM12-A-5-MP-BR-M16-0.25-200

Packing unit: 1



MECHANICAL PROPERTIES

Design:	Bulkhead receptacle
Version:	Straight
Coding:	A
Number of contacts:	5
Connection type:	Crimp / Moulded
Contact type:	Pin contact
Number of mating cycles (min.):	200
Wire section [mm²]:	0.25
Cable length [mm]:	200
Shell material:	Zinc cast
Surface:	Electroless nickel

MECHANICAL PROPERTIES

RoHS-compliant:	Compliant with exception 6c (copper alloy $\leq$ 4% lead)
REACH-compliant:	SVHC substances, yes - Lead
Contact Material:	AU over copper alloy
EMI:	Shell contact

THERMAL PROPERTIES

Material contact insert:	Polyamide (PA)
--------------------------	----------------


ELECTRICAL PROPERTIES

Insulation resistance (Ω):	$\geq 10^{10}$
Potential drop between contacts and housing [kV]:	0.84
Potential drop across contacts [kV]:	0.84
Pollution degree:	3
Rated DC voltage [V]:	63
Rated current [A]:	4

STANDARDS

Fire protection class EN 45545-2:	R23: HL1/HL2/HL3
Fire protection class NF F 16-101 / NF F 16-102:	I2/F2
Protection class EN 60529 (mounted):	IP67
RoHS-compliant:	Compliant with exception 6c (copper alloy $\leq$ 4% lead)
REACH-compliant:	SVHC substances, yes - Lead

DIMENSIONS



DIMENSIONS

L1 [mm]:	23.0
L2 [mm]:	200.0
L3 [mm]:	2.5 - 4.5
N1:	M12x1
N2:	M16x1.5
WS1:	18

· Please contact your Gimota partner for other M12 products