

Pin contact housing D-SUB - 2-poles

Item number: SUH02W2P

Packing unit:




TECHNICAL CHARACTERISTICS

Size:	1
Shell material:	Steel
Surface:	Tin plated
Material contact insert:	Thermoplastic
Operation temperature [°C]:	-55 - +105

STANDARDS

Flammability rating UL 94:	UL94 - V0
----------------------------	-----------

DIMENSIONS



DIMENSIONS


L1 [mm]:	30.8
L2 [mm]:	25.8
Height [mm]:	12.5
T1 [mm]:	3.0

SUB-D pin contact, AWG 22 - 18

Item number: SUMCP18-22AU2

Product weight (kg): 0.0001 kg

Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type: Pin

Contact Material: CU alloy


Protective layer: Gold plated, 0.8µm

Connection type: Crimp

Wire section [mm²]: 0.34 - 1.00

Wire section [AWG]: 22 - 18

DIMENSIONS



DIMENSIONS



D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.4
L1 [mm]:	14.0

SUB-D pin contact, size 8, AWG 20 - 16

Item number: SUMCP8-18AU2

Product weight (kg): 0.0016 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.5 - 1.3
Wire section [AWG]:	20 - 16

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	2.6
D2 Ø [mm]:	3.6
d1 Ø [mm]:	1.7
L1 [mm]:	22.7

SUB-D pin contact, AWG 24 - 20

Item number: SUPCP20-24AU2


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.2 - 0.56
Wire section [AWG]:	24 - 20

DIMENSIONS



DIMENSIONS


L1 [mm]:	14.6
L2 [mm]:	1.7

SUB-D pin contact, AWG 24 - 20, 350 pcs

Item number: SUPCP20-24AU2-3

Product weight (kg): 0.0859 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.2 - 0.56
Wire section [AWG]:	24 - 20

DIMENSIONS





DIMENSIONS

L1 [mm]:	14.6
L2 [mm]:	1.7

SUB-D pin contact, size 8, AWG 20 - 16

Item number: SUMCP8-18AU1


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	0.5 - 1.3
Wire section [AWG]:	20 - 16

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	2.6
D2 Ø [mm]:	3.6
d1 Ø [mm]:	1.7
L1 [mm]:	22.7

SUB-D pin contact, AWG 24 - 20, 1000 pcs

Item number: SUPCP20-24AU2-100


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.2 - 0.56
Wire section [AWG]:	24 - 20

DIMENSIONS





DIMENSIONS

L1 [mm]:	14.6
L2 [mm]:	1.7

SUB-D pin contact, size 8, AWG 12 - 10

Item number: SUMCP8-11AU1


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	3.3 - 6.6
Wire section [AWG]:	12 - 10

DIMENSIONS





DIMENSIONS

D1 Ø [mm]:	4.7
D2 Ø [mm]:	3.6
d1 Ø [mm]:	3.7
L1 [mm]:	22.7

SUB-D pin contact, size 8, AWG 14 - 12

Item number: SUMCP8-14AU2


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	2.0 - 3.3
Wire section [AWG]:	14 - 12

DIMENSIONS





DIMENSIONS

D1 Ø [mm]:	3.6
D2 Ø [mm]:	3.6
d1 Ø [mm]:	2.6
L1 [mm]:	22.7

SUB-D pin contact, size 8, AWG 12 - 10

Item number: SUMCP8-11AU2


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	3.3 - 6.6
Wire section [AWG]:	12 - 10

DIMENSIONS



DIMENSIONS


D1 Ø [mm]:	4.7
D2 Ø [mm]:	3.6
d1 Ø [mm]:	3.7
L1 [mm]:	22.7

SUB-D pin contact, AWG 24 - 20

Item number: SUMCP20-24AU1

Product weight (kg): 0.0001 kg

Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type: Pin

Contact Material: CU alloy


Protective layer: Gold plated, 1.3µm

Connection type: Crimp

Wire section [mm²]: 0.25 - 0.75

Wire section [AWG]: 24 - 20

DIMENSIONS





DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.1
L1 [mm]:	14.0

SUB-D pin contact, size 8, AWG 10 - 8

Item number: SUMCP8-8AU2


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	5.2 - 8.3
Wire section [AWG]:	10 - 8

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	5.8
D2 Ø [mm]:	3.6
d1 Ø [mm]:	4.6
L1 [mm]:	22.7

SUB-D pin contact, AWG 22 - 18

Item number: SUMCP18-22AU1


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	0.34 - 1.00
Wire section [AWG]:	22 - 18

DIMENSIONS





DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.4
L1 [mm]:	14.0

SUB-D pin contact, size 8, AWG 10 - 8


Item number: SUMCP8-8AU1

Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	5.2 - 8.3
Wire section [AWG]:	10 - 8





D1 Ø [mm]:	5.8
D2 Ø [mm]:	3.6
d1 Ø [mm]:	4.6
L1 [mm]:	22.7

SUB-D pin contact, size 8, AWG 14 - 12

Item number: SUMCP8-14AU1

Product weight (kg): 0.002 kg

Packing unit: 50



MECHANICAL PROPERTIES CONTACTS

Contact type: Pin

Contact Material: CU alloy


Protective layer: Gold plated, 1.3µm

Connection type: Crimp

Wire section [mm²]: 2.0 - 3.3

Wire section [AWG]: 14 - 12

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	3.6
D2 Ø [mm]:	3.6
d1 Ø [mm]:	2.6
L1 [mm]:	22.7