

Pin contact housing D-SUB - 9-poles

Item number: SUH09P

Product weight (kg): 0.0045 kg

Packing unit:




TECHNICAL CHARACTERISTICS

Size:	1
Shell material:	Steel
Surface:	Tin plated
Material contact insert:	Thermoplastic
Operation temperature [°C]:	-55 - +105

STANDARDS

Flammability rating UL 94:	UL94 - V0
----------------------------	-----------

DIMENSIONS




DIMENSIONS

L1 [mm]:	30.8
L2 [mm]:	25.8
Height [mm]:	12.5
T1 [mm]:	3.0

SUB-D pin contact, AWG 24 - 20

Item number: SUMCP20-24AU2


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.25 - 0.75
Wire section [AWG]:	24 - 20

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.1
L1 [mm]:	14.0

SUB-D pin contact, AWG 22 - 18


Item number: SUMCP18-22AU2
Product weight (kg): 0.0001 kg
Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.34 - 1.00
Wire section [AWG]:	22 - 18

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.4
L1 [mm]:	14.0

SUB-D pin contact, AWG 22 - 18

Item number: SUMCP18-22AU1


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	0.34 - 1.00
Wire section [AWG]:	22 - 18

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.4
L1 [mm]:	14.0

SUB-D pin contact, AWG 24 - 20, 1000 pcs

Item number: SUPCP20-24AU2-100


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.2 - 0.56
Wire section [AWG]:	24 - 20

DIMENSIONS



DIMENSIONS

L1 [mm]:	14.6
L2 [mm]:	1.7

SUB-D pin contact, AWG 24 - 20

Item number: SUMCP20-24AU1

Product weight (kg): 0.0001 kg


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	0.25 - 0.75
Wire section [AWG]:	24 - 20

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	1.1
L1 [mm]:	14.0

SUB-D pin contact, AWG 24 - 20, 350 pcs

Item number: SUPCP20-24AU2-3

Product weight (kg): 0.0859 kg


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.2 - 0.56
Wire section [AWG]:	24 - 20

DIMENSIONS




DIMENSIONS

L1 [mm]:	14.6
L2 [mm]:	1.7

SUB-D pin contact, AWG 24 - 20

Item number: SUPCP20-24AU2


Packing unit:



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.2 - 0.56
Wire section [AWG]:	24 - 20

DIMENSIONS




DIMENSIONS

L1 [mm]:	14.6
L2 [mm]:	1.7

SUB-D pin contact, AWG 28 - 24

Item number: SUMCP24-28AU1


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 1.3µm
Connection type:	Crimp
Wire section [mm²]:	0.08 - 0.20
Wire section [AWG]:	28 - 24

DIMENSIONS




DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	0.6
L1 [mm]:	14.0

SUB-D pin contact, AWG 28 - 24

Item number: SUMCP24-28AU2


Packing unit: 100



MECHANICAL PROPERTIES CONTACTS

Contact type:	Pin
Contact Material:	CU alloy
Protective layer:	Gold plated, 0.8µm
Connection type:	Crimp
Wire section [mm²]:	0.08 - 0.20
Wire section [AWG]:	28 - 24

DIMENSIONS



DIMENSIONS

D1 Ø [mm]:	1.7
D2 Ø [mm]:	1.0
d1 Ø [mm]:	0.6
L1 [mm]:	14.0